

KVMP 18/13,5-Z10

Cable gland circular, brass, DIN 89280, M18-Pg13,5



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



| | |
|---------------------------------|-----------------------|
| Material cable gland | Brass |
| Material sealing gasket | EPDM |
| Material earthing insert | Brass chromium-plated |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP54 |
| Thread type | PG |
| Ø Connection thread D | 13,5 |
| Length screw-in thread L | 8 mm |
| Ø cable diameter min | 8 mm |
| Ø cable diameter max | 10,5 mm |
| Key width SW | 19 mm |
| Collar diameter (E) | 22 mm |
| Total length TL | 41 mm |
| Install. torques fitting | 10 N m |
| Install. torques cap nut | 10 N m |
| Surface | Bright |
| Order no. bright | 10010917 |
| Type | KVMP 18/13,5-Z10 |
| Packing unit | 1 |

21.09.2018

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:
WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
☎ +49-4191-508-0 · 📠 +49-4191-508-209
contact@wiska.de · www.wiska.com