


KVM 36-W20/Cr

Cable gland, brass chromed-plated, similar to DIN 89280, M36



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



| | |
|---------------------------------|-----------------------|
| Material cable gland | Brass chromium-plated |
| Material sealing gasket | EPDM |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP54 |
| Thread type | M |
| Ø Connection thread D | 36 |
| Lead | 2 |
| Length screw-in thread L | 13 mm |
| Ø cable diameter min | 18 mm |
| Ø cable diameter max | 20,5 mm |
| Key width SW | 36 mm |
| Collar diameter (E) | 34 mm |
| Total length TL | 58 mm |
| Install. torques fitting | 15 N m |
| Install. torques cap nut | 15 N m |
| Surface | Chromium-plated |
| Order no. chrome-plated | 10014581 |
| Type | KVM 36-W20/Cr |
| Packing unit | 1 |

20.08.2018


Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:
WISKA Hoppmann GmbH
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany
☎ +49-4191-508-0 · 📠 +49-4191-508-209
contact@wiska.de · www.wiska.com