


EKVM 36/40-Z22

Enlarging cable gland, brass, DIN 89280, M36-M40



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



| | |
|---------------------------------|-----------------------|
| Material cable gland | Brass |
| Material sealing gasket | EPDM |
| Material earthing insert | Brass chromium-plated |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP54 |
| Thread type | M |
| Ø Connection thread D | 40 |
| Lead | 1,5 |
| Length screw-in thread L | 13 mm |
| Ø cable diameter min | 20 mm |
| Ø cable diameter max | 22,5 mm |
| Key width SW1 | 36 mm |
| Key width SW2 | 46 mm |
| Collar diameter E1 | 39 mm |
| Collar diameter E2 | 50 mm |
| Total length TL | 56 mm |
| Install. torques fitting | 15 N m |
| Install. torques cap nut | 15 N m |
| Surface | Bright |
| Order no. bright | 10016318 |
| Type | EKVM 36/40-Z22 |
| Packing unit | 1 |
| ETIM-Classification | EC000441 |

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

Recommended accessories

GM 36

50011422

22.11.2018

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

