


## KVMS 80-W61

Cable gland, brass, similar to DIN 89280, M80



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



<b>Material cable gland</b>	Brass
<b>Material sealing gasket</b>	EPDM
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP54
<b>Thread type</b>	M
<b>Ø Connection thread D</b>	80
<b>Lead</b>	2
<b>Length screw-in thread L</b>	18 mm
<b>Ø cable diameter min</b>	59 mm
<b>Ø cable diameter max</b>	62 mm
<b>Key width SW1</b>	85 mm
<b>Key width SW2</b>	90 mm
<b>Collar diameter E1</b>	92 mm
<b>Collar diameter E2</b>	100 mm
<b>Total length TL</b>	79 mm
<b>Install. torques fitting</b>	30 N m
<b>Install. torques cap nut</b>	30 N m
<b>Surface</b>	Bright
<b>Order no. bright</b>	10016450
<b>Type</b>	KVMS 80-W61
<b>Packing unit</b>	1
<b>ETIM-Classification</b>	EC000441

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

Recommended accessories

**GM 80**

50011426

15.08.2018

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

