


KVMS 56-W41/Ni

Cable gland, brass nickel-plated, DIN 89280, M56



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



| | |
|---------------------------------|---------------------|
| Material cable gland | Brass nickel-plated |
| Material sealing gasket | EPDM |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP54 |
| Thread type | M |
| Ø Connection thread D | 56 |
| Lead | 2 |
| Length screw-in thread L | 15 mm |
| Ø cable diameter min | 38 mm |
| Ø cable diameter max | 41,5 mm |
| Key width SW1 | 55 mm |
| Key width SW2 | 62 mm |
| Collar diameter E1 | 61 mm |
| Collar diameter E2 | 68 mm |
| Total length TL | 68 mm |
| Install. torques fitting | 20 N m |
| Install. torques cap nut | 15 N m |
| Surface | Nickel-plated |
| Order no. nickel-plated | 10016716 |
| Type | KVMS 56-W41/Ni |
| Packing unit | 1 |
| ETIM-Classification | EC000441 |

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

Recommended accessories

GM 56/Ni

10011557

16.08.2018

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

