


## KVMS 80-Z64/Ni

Cable gland, brass nickel-plated, similar to DIN 89280, M80



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



<b>Material cable gland</b>	Brass nickel-plated
<b>Material sealing gasket</b>	EPDM
<b>Material earthing insert</b>	Brass chromium-plated
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP54
<b>Thread type</b>	M
<b>Ø Connection thread D</b>	80
<b>Lead</b>	2
<b>Length screw-in thread L</b>	18 mm
<b>Ø cable diameter min</b>	62 mm
<b>Ø cable diameter max</b>	66 mm
<b>Key width SW1</b>	85 mm
<b>Key width SW2</b>	90 mm
<b>Collar diameter E1</b>	92 mm
<b>Collar diameter E2</b>	100 mm
<b>Total length TL</b>	79 mm
<b>Install. torques fitting</b>	30 N m
<b>Install. torques cap nut</b>	30 N m
<b>Advice</b>	* Similar to DIN 89280
<b>Surface</b>	Nickel-plated
<b>Order no. nickel-plated</b>	10016747
<b>Type</b>	KVMS 80-Z64/Ni
<b>Packing unit</b>	1
<b>ETIM-Classification</b>	EC000441

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

Recommended accessories

**GM 80/Ni**

10014199

20.08.2018

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

 +49-4191-508-0 ·  +49-4191-508-209

[contact@wiska.de](mailto:contact@wiska.de) · [www.wiska.com](http://www.wiska.com)

