

NSKV 1/4

Cable gland, polyamide, NPT 1/4", RAL 7035



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



| | |
|--------------------------|---------------------------|
| Material cable gland | Polyamide |
| Material sealing gasket | EPDM |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP69, IP68 (5 bar 30 min) |
| Thread type | NPT |
| Ø Connection thread D | 1/4" |
| Length screw-in thread L | 15 mm |
| Ø cable diameter min | 3 mm |
| Ø cable diameter max | 7 mm |
| Ø cable diameter UL | 4,1 mm - 6 mm |
| Key width SW | 16 mm |
| Collar diameter (E) | 18 mm |
| Total length TL | 33 mm - 38 mm |
| Glow wire test | 750 °C |
| Type of cable anchorage | A |
| Install. torques cap nut | 2 N m |
| Install. torques fitting | 2 N m |
| Impact category | 2 |
| Product Color | RAL 9005 |
| Order no. RAL 9005 | 10061854 |
| Type | NSKV 1/4 |
| Packing unit | 50 |
| ETIM-Classification | EC000441 |

Recommended accessories

| | |
|---------------|----------|
| RDE 12 | 10062183 |
| BS 7 | 10064005 |

24.11.2017

