


## NSKV 3/4 LT

Cable gland LowTemp, polyamide, NPT 3/4", RAL 7035



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



<b>Material cable gland</b>	Polyamide
<b>Material sealing gasket</b>	Silicone
<b>Temp. range min</b>	-60 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP69, IP68 (5 bar 30 min)
<b>Thread type</b>	NPT
<b>Ø Connection thread D</b>	3/4"
<b>Length screw-in thread L</b>	15 mm
<b>Ø cable diameter min</b>	9 mm
<b>Ø cable diameter max</b>	17 mm
<b>Key width SW</b>	29 mm
<b>Collar diameter (E)</b>	32 mm
<b>Total length TL</b>	44 mm - 53 mm
<b>Glow wire test</b>	750 °C
<b>Type of cable anchorage</b>	A
<b>Install. torques fitting</b>	10 N m
<b>Install. torques cap nut</b>	4 N m
<b>Product Color</b>	RAL 7035
<b>Order no. RAL 7035</b>	10061870
<b>Type</b>	NSKV 3/4 LT
<b>Packing unit</b>	50

Recommended accessories

RDE 25 LT	10063910
<b>BS 17</b>	10064012
<b>EADR 25/90 LT</b>	10105707

24.11.2017

