


## ESKV-L 40 LT

Cable gland LowTemp, polyamide, M40, RAL 9005 with long thread



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



|                          |                                |
|--------------------------|--------------------------------|
| Material cable gland     | Polyamide                      |
| Material sealing gasket  | Silicone                       |
| Protection class         | IP69, IP68 (5 bar 30 min)      |
| Temp. range min          | -60 °C                         |
| Temp. range max          | 100 °C                         |
| Glow wire test           | 750 °C                         |
| Thread type              | M                              |
| Ø Connection thread D    | 40                             |
| Lead                     | 1,5                            |
| Length screw-in thread L | 18 mm                          |
| Ø cable diameter min     | 16 mm                          |
| Ø cable diameter max     | 28 mm                          |
| Key width SW             | 46 mm                          |
| Collar diameter (E)      | 51 mm                          |
| Total length TL          | 58 mm - 71 mm                  |
| Type of cable anchorage  | A                              |
| Install. torques fitting | 20 N m                         |
| Install. torques cap nut | 20 N m                         |
| Impact category          | 4                              |
| Equipment                | Incl. connection thread gasket |
| Product Color            | RAL 9005                       |
| Type                     | ESKV-L 40 LT                   |
| Order no. RAL 9005       | 10061950                       |
| Packing unit             | 10                             |
| ETIM-Classification      | EC000441                       |

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

Recommended accessories



|                  |          |
|------------------|----------|
| <b>RDE 40 LT</b> | 10063960 |
| <b>BS 28</b>     | 10064016 |

18.08.2018

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

 +49-4191-508-0 ·  +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com