

ESKV-F 12

Cable gland flame-retardant, polyamide, M12, RAL 7035



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



| | |
|---------------------------------|----------------------------|
| Material cable gland | Polyamide, flame-retardant |
| Material sealing gasket | EPDM |
| Protection class | IP69, IP68 (5 bar 30 min) |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Glow wire test | 960 °C |
| Thread type | M |
| Ø Connection thread D | 12 |
| Lead | 1,5 |
| Length screw-in thread L | 9 mm |
| Ø cable diameter min | 3 mm |
| Ø cable diameter max | 7 mm |
| Key width SW | 16 mm |
| Collar diameter (E) | 18 mm |
| Total length TL | 29 mm - 34 mm |
| Type of cable anchorage | A |
| Install. torques fitting | 2 N m |
| Install. torques cap nut | 2 N m |
| Product Color | RAL 7035 |
| Type | ESKV-F 12 |
| Order no. RAL 7035 | 10064626 |
| Packing unit | 50 |
| ETIM-Classification | EC000441 |

Recommended accessories

| | |
|----------------------|----------|
| EMUF 12 | 10060810 |
| RDE 12 | 10062183 |
| EADR 12 | 10062801 |
| BS 7 | 10064005 |
| MFD 12/04/020 | 10064392 |
| MFD 12/02/020 | 10100525 |

18.03.2018

