


SKV 48

Cable gland, polyamide, Pg 48, RAL 7035



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



| | |
|---------------------------------|---------------------|
| Material cable gland | Polyamide |
| Material sealing gasket | EPDM |
| Temp. range min | -40 °C |
| Temp. range max | 100 °C |
| Protection class | IP68 (5 bar 30 min) |
| Thread type | PG |
| Ø Connection thread D | 48 |
| Length screw-in thread L | 15 mm |
| Ø cable diameter min | 36 mm |
| Ø cable diameter max | 44 mm |
| Key width SW | 65 mm |
| Collar diameter (E) | 73 mm |
| Total length TL | 60 mm - 68 mm |
| Glow wire test | 750 °C |
| Type of cable anchorage | A |
| Product Color | RAL 7035 |
| Order no. RAL 7035 | 10066409 |
| Type | SKV 48 |
| Packing unit | 4 |
| ETIM-Classification | EC000441 |

Recommended accessories

| | |
|---------------|----------|
| MUG 48 | 10060679 |
|---------------|----------|

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com

ADR 48

10061428

BS 38

10064018

15.08.2018

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com