

## NSKV-RDE 1/2

Cable gland with reduction sealing insert, polyamide, NPT 1/2", RAL 9005



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



<b>Material cable gland</b>	Polyamide
<b>Material sealing gasket</b>	EPDM
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP68 (5 bar 30 min), IP69
<b>Thread type</b>	NPT
<b>Ø Connection thread D</b>	1/2"
<b>Length screw-in thread L</b>	15 mm
<b>Ø cable diameter min</b>	4 mm
<b>Ø cable diameter max</b>	13 mm
<b>Key width SW</b>	24 mm
<b>Collar diameter (E)</b>	27 mm
<b>Total length TL</b>	42 mm - 51 mm
<b>Glow wire test</b>	750 °C
<b>Type of cable anchorage</b>	A
<b>Install. torques cap nut</b>	3 N m
<b>Install. torques fitting</b>	4 N m
<b>Advice</b>	With reduction insert
<b>Product Color</b>	RAL 9005
<b>Order no. RAL 9005</b>	10101984
<b>Type</b>	NSKV-RDE 1/2
<b>Packing unit</b>	50

14.08.2018


Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com