

## NSKV-RDE 2

Cable gland with reduction sealing insert, polyamide, NPT 2", RAL 9005



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



|                                 |                           |
|---------------------------------|---------------------------|
| <b>Material cable gland</b>     | Polyamide                 |
| <b>Material sealing gasket</b>  | EPDM                      |
| <b>Temp. range min</b>          | -40 °C                    |
| <b>Temp. range max</b>          | 100 °C                    |
| <b>Protection class</b>         | IP68 (5 bar 30 min), IP69 |
| <b>Thread type</b>              | NPT                       |
| <b>Ø Connection thread D</b>    | 2"                        |
| <b>Length screw-in thread L</b> | 18 mm                     |
| <b>Ø cable diameter min</b>     | 28 mm                     |
| <b>Ø cable diameter max</b>     | 48 mm                     |
| <b>Key width SW</b>             | 68 mm                     |
| <b>Collar diameter (E)</b>      | 75 mm                     |
| <b>Total length TL</b>          | 69 mm - 83 mm             |
| <b>Glow wire test</b>           | 750 °C                    |
| <b>Type of cable anchorage</b>  | A                         |
| <b>Install. torques cap nut</b> | 30 N m                    |
| <b>Install. torques fitting</b> | 30 N m                    |
| <b>Advice</b>                   | With reduction insert     |
| <b>Product Color</b>            | RAL 9005                  |
| <b>Order no. RAL 9005</b>       | 10101992                  |
| <b>Type</b>                     | NSKV-RDE 2                |
| <b>Packing unit</b>             | 3                         |

24.11.2017

WISKA Hoppmann GmbH  
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany  
☎ +49-4191-508-0 · 📠 +49-4191-508-209  
contact@wiska.de · www.wiska.com

