

NSKV-RDE 1/4

Cable gland with reduction sealing insert, polyamide, NPT 1/4", RAL 7035



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



Material cable gland	Polyamide
Material sealing gasket	EPDM
Temp. range min	-40 °C
Temp. range max	100 °C
Protection class	IP68 (5 bar 30 min), IP69
Thread type	NPT
Ø Connection thread D	1/4"
Length screw-in thread L	15 mm
Ø cable diameter min	1 mm
Ø cable diameter max	7 mm
Key width SW	16 mm
Collar diameter (E)	18 mm
Total length TL	33 mm - 38 mm
Glow wire test	750 °C
Type of cable anchorage	A
Install. torques cap nut	2 N m
Install. torques fitting	2 N m
Advice	With reduction insert
Product Color	RAL 7035
Order no. RAL 7035	10102679
Type	NSKV-RDE 1/4
Packing unit	50

16.08.2018

Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

WISKA Hoppmann GmbH

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com