

## NSKV-RDE 1/4

Cable gland with reduction sealing insert, polyamide, NPT 1/4", RAL 7035



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



|                          |                           |
|--------------------------|---------------------------|
| Material cable gland     | Polyamide                 |
| Material sealing gasket  | EPDM                      |
| Temp. range min          | -40 °C                    |
| Temp. range max          | 100 °C                    |
| Protection class         | IP68 (5 bar 30 min), IP69 |
| Thread type              | NPT                       |
| Ø Connection thread D    | 1/4"                      |
| Length screw-in thread L | 15 mm                     |
| Ø cable diameter min     | 1 mm                      |
| Ø cable diameter max     | 7 mm                      |
| Key width SW             | 16 mm                     |
| Collar diameter (E)      | 18 mm                     |
| Total length TL          | 33 mm - 38 mm             |
| Glow wire test           | 750 °C                    |
| Type of cable anchorage  | A                         |
| Install. torques cap nut | 2 N m                     |
| Install. torques fitting | 2 N m                     |
| Advice                   | With reduction insert     |
| Product Color            | RAL 7035                  |
| Order no. RAL 7035       | 10102679                  |
| Type                     | NSKV-RDE 1/4              |
| Packing unit             | 50                        |

22.11.2017

WISKA Hoppmann GmbH  
Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany  
☎ +49-4191-508-0 · 📠 +49-4191-508-209  
contact@wiska.de · www.wiska.com

