

## NSKV-RDE 3/8

Cable gland with reduction sealing insert, polyamide, NPT 3/8", RAL 7035



Product illustrations are exemplary and may differ from the chosen product. Further variants and individual customization, we will gladly provide you on request.



<b>Material cable gland</b>	Polyamide
<b>Material sealing gasket</b>	EPDM
<b>Temp. range min</b>	-40 °C
<b>Temp. range max</b>	100 °C
<b>Protection class</b>	IP68 (5 bar 30 min), IP69
<b>Thread type</b>	NPT
<b>Ø Connection thread D</b>	3/8"
<b>Length screw-in thread L</b>	15 mm
<b>Ø cable diameter min</b>	2 mm
<b>Ø cable diameter max</b>	10 mm
<b>Key width SW</b>	20 mm
<b>Collar diameter (E)</b>	22 mm
<b>Total length TL</b>	35 mm - 41 mm
<b>Glow wire test</b>	750 °C
<b>Type of cable anchorage</b>	A
<b>Install. torques cap nut</b>	1,5 N m
<b>Install. torques fitting</b>	3,5 N m
<b>Advice</b>	With reduction insert
<b>Product Color</b>	RAL 7035
<b>Order no. RAL 7035</b>	10102680
<b>Type</b>	NSKV-RDE 3/8
<b>Packing unit</b>	50

21.08.2018

Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com



Your Contact:

**WISKA Hoppmann GmbH**

Kisdorfer Weg 28 · 24568 Kaltenkirchen · Germany

☎ +49-4191-508-0 · 📠 +49-4191-508-209

contact@wiska.de · www.wiska.com